command-line

NAME

command-line - Command line

DESCRIPTION

The mkdocs-exporter command exports websites built by Zensical (experimental): run it once the website is built. With MkDocs and ProperDocs, use the plugin instead: it exports documents while the website is built.

SECTIONS

01 mkdocs-exporter build
02 mkdocs-exporter

SEE ALSO

front-matter, css-classes-and-attributes, javascript-hooks

Command line

The `mkdocs-exporter` command exports websites built by Zensical (experimental): run it once the website is built. With MkDocs and ProperDocs, use the plugin instead: it exports documents while the website is built.

`mkdocs-exporter build`

Exports the website whose configuration file is found in the current directory (`zensical.toml`, `mkdocs.yml` or `mkdocs.yaml`, in that order), with the options of its `exporter` plugin.

Option	Effect
`-f`, `--config-file FILE`	The configuration file of the website
`-s`, `--strict`	Fails when warnings are logged
`-v`, `--verbose`	Logs details (the `debug` level)
`--help`	Shows the options

The command exits with the status `1` when the website can't be exported (missing or invalid configuration, invalid front matter, missing browser...), when pages fail to render, or when warnings are logged with `--strict`.

`mkdocs-exporter`

Option	Effect
`--version`	Shows the version of the plugin
`--help`	Shows the commands

COLOPHON

This document is a page of https://adrienbrignon.github.io/mkdocs-exporter/, printed by MkDocs Exporter 7.0.0 with Chromium.